





A fashionable and friendly entry-level Gigabit IP phone, Yealink T31G has an extra-large 132x64-pixel graphical LCD with backlight that brings clear visual experience for users. The T31G offers support for two VoIP accounts and includes local 5-way conferencing to maximize productivity.

Working with an adjustable multi-angle stand or the ability to wall mount, the T31G allows for flexible usage and application. It also boasts built-in Power over Ethernet (POE) and superb high definition (HD) sound quality. Easy-to-use and powerful features together with a reasonable price, deliver an excellent voice communications solution.

<p>Audio Features</p> <ul style="list-style-type: none"> • HD voice: HD handset, HD speaker • Smart Noise Filtering • Wideband codec: Opus, G.722 • Narrowband codec: G.711(A/μ), G.723.1, G.729, G.729A, G.726, ILBC • DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO • Full-duplex hands-free speakerphone with AEC • VAD, CNG, AEC, PLC, AJB, AGC <p>Phone Features</p> <ul style="list-style-type: none"> • 2 VoIP accounts • Call hold, mute, DND • One-touch speed dial, hotline • Call forward, call waiting, call transfer • Group listening, SMS, emergency call • Redial, call return, auto answer • Local 5-way conferencing • Direct IP call without SIP proxy • Ring tone selection/import/delete • Set date time manually or automatically • Dial plan • XML Browser, action URL/URI • Integrated screenshots • RTPC-XR, VO-RTCPXR • Enhanced DSS Key <p>Directory</p> <ul style="list-style-type: none"> • Local phonebook up to 1000 entries • Black list • XML/LDAP remote phonebook • Smart dialing • Phonebook search/import/export • Call history: dialed/received/missed/forwarded <p>IP-PBX Features</p> <ul style="list-style-type: none"> • Busy Lamp Field (BLF), Bridged Line Appearance (BLA) • Anonymous call, anonymous call rejection • Hot-desking, voice mail • Flexible seating • Call park, call pickup • Executive and Assistant • Centralized call recording • Visual voice mail • Call recording 	<p>Display and Indicator</p> <ul style="list-style-type: none"> • 2.3" 132x64-pixel graphical LCD with backlight • LED for call and message waiting indication • Dual-color (red or green) illuminated LEDs for line status information • Intuitive user interface with icons and soft keys • Multilingual user interface • Caller ID with name and number • Power saving <p>Feature keys</p> <ul style="list-style-type: none"> • 2 line keys with LED • 6 features keys: transfer, message, headset, redial, mute, hands-free speakerphone • 5 navigation keys • Volume control keys <p>Interface</p> <ul style="list-style-type: none"> • Dual-port Gigabit Ethernet • Power over Ethernet (IEEE 802.3af), class 2 • 1 x RJ9 (4P4C) handset port • 1 x RJ9 (4P4C) headset port <p>Other Physical Features</p> <ul style="list-style-type: none"> • Color: Classic Grey • Wall mountable • External Yealink AC adapter • AC 100-240V input and DC 5V/600mA output • Power consumption (PSU): 2-3W • Power consumption (PoE): 3-4W • Dimension (W*D*H*): 188mm*189mm*162mm*50mm • Operating humidity: 10-95% • Operating temperature: -10-50°C (+14-122°F) <p>Management</p> <ul style="list-style-type: none"> • Configuration: browser/phone/auto-provision • Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy • Auto-provision with PnP • Zero-sp-touch, TR-069 • Phone lock for personal privacy protection • Reset to factory, reboot • Package tracing export, system log 	<p>Network and Security</p> <ul style="list-style-type: none"> • SIP v1 (RFC2543), v2 (RFC3261) • Call server redundancy supported • NAT traversal: STUN mode • Proxy mode and peer-to-peer SIP link mode • IP assignment: static/DHCP • HTTP/HTTPS web server • Time and date synchronization using NTP • UDP/TCP/DNS-SRV (RFC 3263) • QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP • SRTP for voice • Transport Layer Security (TLS) • HTTPS certificate manager • AES encryption for configuration file • Digest authentication • OpenVPN, IEEE802.1X • IPv6 • LLDAP/CDP/DHCP VLAN • ICE <p>Package Features</p> <ul style="list-style-type: none"> • Package content: <ul style="list-style-type: none"> - Yealink SIP-T31G IP phone - Handset with handset cord - Ethernet Cable (1.5m CAT5E UTP Cable) - Stand - Quick Start Guide - Power Adapter (Optional) • Qty/CTN: 10 PCS • N.W/CTN: 9.98 kg • G.W/CTN: 10.836 kg • Giftbox size: 213 mm*210 mm*103 mm • Carton Meas: 535 mm*443 mm*227 mm <p>Compliance</p> <p>  </p> <p>  </p>
--	--	--

