



7-inch  
Multitouch  
Screen



Adjustable  
Corded-Cordless  
Phone



Content  
Sharing



Opus  
Codec



HD  
Audio



Built-in  
Bluetooth



Built-in  
Wi-Fi



USB 2.0



Especially designed for busy executives and professionals, Yealink SIP-T57W is an easy-to-use Prime Business Phone with an adjustable 7-inch multi-point touch screen that allows you to easily find a comfortable viewing angle, according to personal and environmental needs, as well as get rich visual presentation and easy navigation with just one-touch.

With the built-in Bluetooth 4.2 and the built-in dual band 2.4G/5G Wi-Fi, the SIP-T57W IP Phone ensures that you keep up with and are on the cutting edge of this ever changing modern wireless age.

Its built-in USB 2.0 port allows for USB recording or a direct wired/wireless USB headset or up to three Yealink EXP50 expansion modules connection. Benefiting from these features, the Yealink SIP-T57W is a powerful and expandable office phone that delivers optimum desktop efficiency and productivity.

## Audio Features

- HD voice: HD handset, HD speaker
- Hearing aid compatible (HAC) handset
- Acoustic Shield
- Smart Noise Filtering
- Audio codec: Opus, G.722, PCMU (G.711A), PCMA (G.711µ), G.729, G.729A, G.729B, G.729AB, G.726, G.723.1, iLBC
- DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, CNG, AEC, PLC, AJB, AGC

## Phone Features

- 16 VoIP accounts
- One-touch speed dial, hotline
- Call forward, call waiting, call transfer
- Mute, DND, call hold, redial, call return, auto answer
- Group listening, SMS, emergency call
- 10-way conferencing
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Set date time manually or automatically
- Dial plan, XML Browser, Action URL/URI
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
- Built-in dual band Wi-Fi:
  - Network standard: IEEE802.11a/b/g/n
  - Transmission rate: Up to 433Mbps (dynamic)
  - Frequency range: 2.4GHz/5.0GHz
- Built-in Bluetooth for:
  - Bluetooth headset,
  - Mobile contacts synchronization
  - Bluetooth call
  - Simultaneous connection of one headset and one mobile phone
- USB port (2.0 compliant) for:
  - Wired/wireless USB headset
  - USB call recording through USB flash drive
  - Color-screen expansion modules EXP50 (up to 3)
  - Wireless Headset Adapter EHS40
- USB/Bluetooth connectivity to Yealink CP900/CP700 speakerphone, USB connectivity to Yealink UH36 headset:
  - Basic functions: Answer / end, call mute
  - Enhanced function: audio optimization, redial, call hold, volume synchronization, multiple calls control
- Content Sharing (via Yealink VCD)
- Enhanced DSS key

## Directory

- Local phonebook up to 1000 entries
- Black list
- XML/LDAP remote phonebook
- Smart dialing
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded

## Corded-Cordless Phone (via DECT Dongle DD10K)

- Up to 4 DECT cordless handsets
- Up to 4 concurrent calls
- Support Yealink W52H/W53H/W56H/DD Phone/CP930W
- Slave Handset for Master Deskset

## IP-PBX Features

- Busy Lamp Field (BLF), Bridged Line Appearance (BLA)
- Anonymous call, anonymous call rejection
- Hot-desking, voice mail
- Flexible seating, Executive and Assistant
- Call park, call pickup
- Centralized call recording, call recording

## Display and Indicator

- 7" 800 x 480 capacitive adjustable touch screen
- LED for call and message waiting indication
- Dual-color (red or green) illuminated LEDs for line status information
- Wallpaper
- Intuitive user interface with icons and soft keys
- Multilingual user interface
- Caller ID with name, number and photo
- Screensaver
- Power saving

## Feature keys

- 29 one-touch DSS keys
- 7 feature keys: hold, transfer, message, headset, mute, redial, speakerphone
- Volume control keys
- Illuminated mute/headset/hands-free speakerphone key

## Interface

- Dual-port Gigabit Ethernet
- Power over Ethernet (IEEE 802.3af)
- 1 x USB port (2.0 compliant)
- 1 x RJ9 (4P4C) handset port
- 1 x RJ9 (4P4C) headset port

## Management


- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- Broadsoft device management
- Zero-sp-touch, TR-069
- Phone lock for personal privacy protection
- Reset to factory, reboot
- Package tracing export, system log

## Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- Call server redundancy supported

- NAT traversal: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- SRTP for voice
- Transport Layer Security (TLS 1.3)
- HTTPS certificate manager
- AES encryption for configuration file (AES256)
- Digest authentication using MD5/MD5-sess
- OpenVPN, IEEE802.1X, L2TP VPN
- IPv6, LLDP/CDP/DHCP VLAN, ICE
- WPA2/WPA3
- Secure boot
- GARP (Generic Attribute Registration Protocol)

## Other Physical Features

- Color: Classic Grey
- Wall mountable (optional)
- External Yealink AC adapter (optional): AC 100~240V input and DC 5V/2A output
- USB output currency: 5V  500mA
- Power consumption (PSU): 3.2W-6.3W
- Power consumption (PoE): 4.0W-7.8W
- Dimension (W\*D\*H\*T): 259.4mm\*220mm\*211mm\*44.5mm
- Operating humidity: 10~95%
- Operating temperature: -10~50°C (+14~122°F)

## Package Features

- Package content:
  - Yealink SIP-T57W IP phone
  - Handset with handset cord
  - Ethernet Cable
  - Stand
  - Quick Start Guide
  - Power Adapter (Optional)
- Qty/CTN: 5 PCS
- N.W/CTN: 8.86 kg
- G.W/CTN: 9.79 kg
- Giftbox size: 324 mm\*293 mm\*128 mm
- Carton Meas: 680 mm\* 303 mm\*342 mm

## Compliance

