



* Wireless Microphone is coming soon



Yealink CP935W is a wireless touch-sensitive HD conference phone designed for small to medium conference rooms. Its fingerprint-proof LCD screen with a clear UI interaction page makes it easy to control the meeting.


CP935W has built-in battery and Wi-Fi, you can register a SIP account directly through Wi-Fi. CP935W doesn't require power or network cables, enabling a wireless and clean conference room.

In addition, you can also connect CP935W to your mobile devices through Bluetooth or USB port which supports hybrid UC meetings.

Key Features

- 4-inch multi-touch screen with 480x800 resolution
- Optimal HD audio, full duplex technology
- Yealink Noise Proof Technology
- Built-in rechargeable lithium battery
- Up to 20 hours talk time (in ideal conditions)
- Up to 75 hours standby time in Wi-Fi mode (in ideal conditions)
- 20-foot (6-meter) and 360° voice pickup
- Built-in 6-microphone array for voice pickup
- 5-way conference call
- Hybrid UC meeting
- Built-in Wi-Fi (2.4GHz/5GHz, 802.11a/b/g/n)
- Built-in Bluetooth 4.2

<p>Audio Features</p> <ul style="list-style-type: none"> Optimal HD audio Yealink Noise Proof Technology Smart Noise Filtering 20-foot (6-meter) microphone pickup range Apply to small to medium conference room Built-in 6-microphone array for voice pickup Loudspeaker <ul style="list-style-type: none"> Frequency: 100-20,000 Hz Volume: 94dB at 0.5-m peak volume 56mm diameter and 5w speaker Full-duplex speakerphone with AEC Echo cancellation tail length is up to 320ms Background noise suppression Codecs: G722, G722.1C, G726, G.729, G.729A, G723, iLBC, Opus, PCMU (G.711A), PCMA (G.711μ), AMR DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO VAD, CNG, PLC, AJB, AGC 	<ul style="list-style-type: none"> Blocklist <p>IP-PBX features</p> <ul style="list-style-type: none"> Busy Lamp Field (BLF) Multicast paging Intercom Anonymous call Anonymous call rejection Voice mail Distinctive ringtone Call pickup <p>Display</p> <ul style="list-style-type: none"> 4" 480x800 capacitive touch screen Volume key Home button <p>Interface</p> <ul style="list-style-type: none"> Built-in Wi-Fi (2.4GHz/5GHz, 802.11a/b/g/n) Built-in Bluetooth 4.2 1 x USB 2.0 Type-C device port 1 x Security slot 	<p>Management</p> <ul style="list-style-type: none"> Configuration: browser/phone/auto-provision/Yealink Device Management Platform Auto provision via FTP/TFTP/HTTP/HTTPS for mass deployment Auto-provision with PnP Zero-sp-touch, TR-069 Reset to factory, reboot Package tracing export, system log <p>Other physical features</p> <ul style="list-style-type: none"> Color: Black Wi-Fi range <ul style="list-style-type: none"> Up to 300 meters, depends on Wi-Fi router PSU: 2.2-6W Battery capacity: 7800mAh Charging time: 4 hours Up to 75 hours standby time in Wi-Fi mode (in ideal conditions) Up to 20 hours talk time (in ideal conditions) Dimension (W*D*H): 288.6mm*285.2mm*63.9mm Operating humidity: 10-90% Storage temperature: -10-40°C (+14-104°F)
<p>Phone features</p> <ul style="list-style-type: none"> 1 SIP account Call hold, mute, DND, call recording, hotline 5-way conference call Redial, call waiting, emergency call Call forward, call transfer, call return, dial plan Ring tone selection/import/delete Set date time manually or automatically Volume adjustment Pairing via Bluetooth Create meeting directly Join meeting seamlessly Active Speaker <p>Directory</p> <ul style="list-style-type: none"> Local phonebook up to 1000 entries XML/LDAP remote phonebook Intelligent search method Phonebook search/import/export Call history: dialed/received/missed/forwarded 	<p>Network and Security</p> <ul style="list-style-type: none"> SIP v1 (RFC2543), v2 (RFC3261) SIP server redundancy supported IPv4/IPv6 NAT traversal: STUN mode Proxy mode and peer-to-peer SIP link mode HTTP/HTTPS web server Time and date synchronization using SNTP UDP/TCP/DNS-SRV (RFC 3263) SRTP for voice encryption Transport Layer Security (TLS1.3) HTTPS certificate manager AES encryption for configuration file (AES256) Digest authentication using MD5/MD5-sess OpenVPN, L2TP VPN WPA2 Secure boot 	<p>Package Features</p> <ul style="list-style-type: none"> Package content: <ul style="list-style-type: none"> Yealink CP935W IP conference phone Charger cradle Yealink Power Adapter Wireless Microphone CPW25 (Optional) Quick Start Guide Qty/CTN: 5 PCS N.W/CTN: 7.416 kg G.W/CTN: 8.420 kg Giftbox size: 355mm*349mm*108mm Carton Meas: 567mm*357mm*365mm <p>Compliance</p> <p>CE, FCC, RoHS, REACH, ISO 9001, CCC</p> <p>broadsoft 3CX metaswitch</p>



The datasheet focuses on Wi-Fi mode, please refer to CP935W-Base if you want to learn more about DECT mode.